



FAME SP

**SEVERE
TO
PROFOUND HEARING LOSS**

- Stable class D circuit
- Wheel volume control
- N/H for program switch
- Low battery warning Indicator
- Earhook and thin tube open fit optional
- Streamlined design make you comfortable
- Stay dry and easy to clean

TECHNICAL SPECIFICATIONS

FAME SP		
Measurement	ANSI/IEC 2cc Coupler	IEC OES Coupler
Peak OSPL90 (dB SPL)	137	139
HFA OSPL90 (dB SPL)	131	NA
RTF OSPL90 (dB SPL)	NA	136
Peak Gain (dB)	72	78
HFA Full-On Gain (dB)	67	NA
RTF Full-On Gain (dB)	NA	71
Frequency Range (Hz)	200- 4500	200- 4500
Reference Test Frequency (kHz)	NA	1.6
HFA Frequencies (kHz)	1.0, 1.6, 2.5	NA
Reference Test Gain (dB)	45	50
EIN Level (dBSPL)	<20	<20
Harmonic Distortion		
500 Hz (%)	<3	<3
800 Hz (%)	<2	<2
1600 Hz (%)	<1	<1
Induction Coil Sensitivity		
HFA SPLITS (ANSI) (dB SPL)	92	NA
MASL (IEC) (dB SPL)	NA	97
ANSI/IEC Battery Current (mA)	1.31	1.31
Idle Current (mA)	1.27	1.27
Estimated Battery Life for 16-Hour Day		
675 Zinc Air (days)	16-20	16-20